



### Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Mounting box
Aesthetic name	Unica (standard aesthetic)
Product compatibility	Except stand alone electronics
Device presentation	Assembly
Number of modules	6 modules
Number of gangs	3 gangs
Fixing mode	Pins
Colour tint	White

### Complementary

Provided equipment	Fixing frame
Device mounting	Surface
Cable entry	6 knock-outs
Fire resistance	650 °C @30 s
Material	Box : ASA + PC Fixing frame : PBT (polybutylene terephthalate)
Standards	UNE 60670-1
Depth	28 mm
Width	231 mm
Height	79 mm
Product weight	0.139 kg
Market segment	Residential Small commercial

MGU87.026

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0610 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------