



Main

Range of product	Unica Wireless
Product or component type	Battery powered push-button
Product compatibility	Unica Class cover frames
Switch function	1-way
Transmission frequency	868 MHz
Number of modules	2 modules
Fixing mode	Screws Stucked
Colour tint	Graphite
Device composition	1 large rocker and 2 narrow rockers Flat fixing frame Lithium battery
Provided equipment	Set of 12 symbols

Complementary

Wiring device mounting	Surface
Contacts type and composition	1 NO
Operating distance	Indoor : 10...50 m Outdoor : <= 300 m
Number of batteries	1 CR2032 (lithium): 3 V - autonomy: 5...7 years
Standards	89/336/EEC 99/5/EEC EN 61000-6-2 EN 61001-6-3 ETSI EN 300 220 ETSI EN 301 489
Ambient air temperature for operation	-5...50 °C
Relative humidity	20...95 %
Embedding depth	5 mm
Height	88 mm

Width	96 mm
Depth	19 mm

Environment

IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------