



Main

|                           |                 |
|---------------------------|-----------------|
| Range compatibility       | PacDrive 3      |
| Product or component type | AC servo motors |
| Device short name         | MH3             |

Complementary

|                           |  |
|---------------------------|--|
| Maximum mechanical speed  | 8000 rpm   |
| [Us] rated supply voltage | 115...480 V  |
| Network number of phases  | Three phase  |
| Continuous stall current  | 2.94 A   |
| Continuous stall torque   | 2.48 N.m at 115...480 V three phase  |
| Continuous power          | 1380 W   |
| Peak stall torque         | 7.4 N.m at 115...480 V three phase   |
| Nominal output power      | 0.31 W at 115 V<br>0.7 W at 230 V<br>1.16 W at 400 V<br>1.38 W at 480 V          |
| Nominal torque            | 2.37 N.m at 115 V<br>2.23 N.m at 230 V<br>2.01 N.m at 400 V<br>1.89 N.m at 480 V |
| Nominal speed             | 1250 rpm at 115 V<br>3000 rpm at 230 V<br>5500 rpm at 400 V<br>7000 rpm at 480 V |
| Maximum current Irms      | 9.68 A   |
| Shaft end                 | Smooth shaft   |
| Second shaft              | Without second shaft end   |
| Shaft diameter            | 11 mm  |
| Shaft length              | 23 mm  |
| IP degree of protection   | IP65 (standard)  |

|                                       |  |
|---------------------------------------|--|
| Encoder type                          | Single turn SinCos Hiperface   |
| Speed feedback resolution             | 16 periods   |
| Holding brake                         | With   |
| Holding torque                        | 3 N.m  |
| Mounting support                      | International standard flange  |
| Motor flange size                     | 70 mm  |
| Electrical connection                 | Rotatable right-angled connectors  |
| Torque constant                       | 0.84 N.m/A at 120 °C   |
| Back emf constant                     | 54.08 V/krpm   |
| Number of motor poles                 | 10   |
| Rotor inertia                         | 1.24 kg.cm <sup>2</sup>  |
| Stator resistance                     | 3.84 Ohm   |
| Stator inductance                     | 12.19 mH   |
| Stator electrical time constant       | 3.2 ms   |
| Maximum radial force Fr               | 390 N at 6000 rpm<br>410 N at 5000 rpm<br>450 N at 4000 rpm<br>490 N at 3000 rpm<br>560 N at 2000 rpm<br>710 N at 1000 rpm |
| Brake pull-in power                   | 7 W  |
| Type of cooling                       | Natural convection   |
| Length                                | 193 mm   |
| Centring collar diameter              | 60 mm  |
| Centring collar depth                 | 2.5 mm   |
| Number of mounting holes              | 4  |
| Mounting holes diameter               | 5.5 mm   |
| Circle diameter of the mounting holes | 82 mm  |
| Product weight                        | 3.3 kg   |
| Sizing reference                      | MH30702P   |
| Temperature copper hot                | 135 °C   |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1328 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |