



### Main

Range compatibility	PacDrive 3
Product or component type	AC servo motors
Device short name	MH3

### Complementary

Maximum mechanical speed	3800 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	30.8 A
Continuous stall torque	48 N.m at 115...480 V three phase
Continuous power	6260 W
Peak stall torque	220 N.m at 115...480 V three phase
Nominal output power	6.07 W at 400 V 6.07 W at 480 V
Nominal torque	29 N.m at 400 V 29 N.m at 480 V
Nominal speed	2000 rpm at 400 V 2000 rpm at 480 V
Maximum current Irms	114 A
Shaft end	Parallel key
Second shaft	Without second shaft end
Shaft diameter	38 mm
Shaft length	80 mm
Key width	10 mm
IP degree of protection	IP65 (standard)
Encoder type	Single turn SinCos Hiperface
Speed feedback resolution	16 periods
Holding brake	Without

Mounting support	International standard flange
Motor flange size	190 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	1.56 N.m/A at 120 °C
Back emf constant	108.3 V/krpm
Number of motor poles	10
Rotor inertia	130.1 kg.cm <sup>2</sup>
Stator resistance	0.15 Ohm
Stator inductance	3.86 mH
Stator electrical time constant	18.7 ms
Maximum radial force Fr	3200 N at 1000 rpm 3100 N at 2000 rpm 3000 N at 3000 rpm 2950 N at 4000 rpm
Type of cooling	Natural convection
Length	250 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Product weight	44 kg
Sizing reference	MH31902P
Temperature copper hot	135 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1343 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations