



Overview

Model Name	APC Microsol Isolator Module 500W, Bivolt/115V, Voltage Regulation (MIE G3 500 Standard)
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Brazil

Output

Number of Outlets	4
Receptacle Style	NBR14136

Input

Input Power	0 W
Input Frequency	60 Hz
Input Connections	NBR 14136
Maximum Line Current per phase	0.0 A
Cord Length	0,91 meters
Maximum Input Current	0 A

Surge Protection and Filtering

EMI/RFI Noise rejection (100 kHz to 10 MHz)	0.0 dB
Peak Current Common Mode	0.0 kA
NM Surge Response Time (ns)	0.0 NS

Physical

Net Weight	7.09 kg
Maximum Height	147.0 mm
Maximum Width	170.0 mm
Maximum Depth	250.0 mm
Shipping Weight	7.44 kg
Shipping Height	153.0 mm

MIE500BI_APC

Shipping Width	173.0 mm
Shipping Depth	265.0 mm
Master Carton Units	1.0
Master Carton Dimensions (Length x Width x Height)	11 x 13 x 7 inches
Master Carton Weight	0.0 lbs
Color	Black
Units per Pallet	0.0

Conformance

Approvals	INMETRO 14.373:2006
Standard warranty	3 years repair or replace