



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Front face
Type of front plate	Transparent
Accessory / separate part category	Installation accessory

### Complementary

Enclosure mounting	Flush
Type of front cover	Transparent
Number of horizontal rows	1
9 mm pitches	8
Number of 18 mm modules per row	4
Total number of 18 mm modules	4
Enclosure material	Door : technoplastic Front face : technoplastic
Width	150 mm outside
Height	252 mm outside
Depth	13 mm wall 17 mm outside
Colour	Door : smoked Front face : white

### Environment

Standards	IEC 529 EN 50102 IEC 60695-2-11
Fire resistance	Door : 650 °C Front face : 750 °C
IK degree of protection	IK07

---

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference contains SVHC above the threshold - Go to CaP for more details <a href="#">Go to CaP for more details</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

---

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---