



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Front face
Type of front plate	Plain
Accessory / separate part category	Installation accessory

Complementary

Enclosure mounting	Flush
Type of front cover	Plain
Number of horizontal rows	2
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	24
Enclosure material	Door : technoplastic Front face : technoplastic
Width	294 mm outside
Height	377 mm outside
Depth	13 mm wall 18 mm outside
Colour	Door : white Front face : white

Environment

Standards	IEC 60695-2-11 EN 50102 IEC 529
Fire resistance	Door : 650 °C Front face : 750 °C
IK degree of protection	IK07

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
