



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	6
Number of horizontal rows	1
Type of front cover	Transparent door
Width	160 mm outside
Height	198 mm outside
Depth	95.5 mm outside

Complementary

Enclosure mounting	Surface
9 mm pitches	12
Total number of 18 mm modules	6
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth terminal block with 4 screwed outgoing 1 neutral terminal block with 4 screwed outgoing
Distribution block outgoing	1 x 16 mm ² for earth 1 x 16 mm ² for neutral 1 x 6 mm ² for earth 1 x 6 mm ² for neutral 2 x 10 mm ² for earth 2 x 10 mm ² for neutral
Enclosure material	Back part : technoplastic Door : technoplastic

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Front face : technoplastic

Colour Door : smoked
Front face : white

Environment

Standards IEC 529
IEC 60695-2-11
IEC 60670-24
EN 50102
IEC 60439-3

Quality labels IMQ

Fire resistance Door : 650 °C
Front face : 750 °C
Back part : 750 °C

IP degree of protection IP40

IK degree of protection IK07

Ambient air temperature for operation -25...60 °C

Offer Sustainability

Sustainable offer status Green Premium product

RoHS (date code: YYWW) Compliant - since 0901 - Schneider Electric declaration of conformity
[Schneider Electric declaration of conformity](#)

REACH Reference contains SVHC above the threshold - Go to CaP for more details
[Go to CaP for more details](#)

Product environmental profile Available
[Product environmental](#)

Product end of life instructions Need no specific recycling operations
[End of life manual](#)

Contractual warranty

Warranty period 18 months