



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	2
Type of front cover	Transparent door
Width	268 mm outside
Height	353 mm outside
Depth	102 mm outside

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	24
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth terminal block with 16 screwed outgoers 1 neutral terminal block with 16 screwed outgoers
Distribution block outgoers	2 x 16 mm ² for earth 2 x 16 mm ² for neutral 6 x 6 mm ² for earth 6 x 6 mm ² for neutral 8 x 10 mm ² for earth 8 x 10 mm ² for neutral
Enclosure material	Back part : technoplastic Door : technoplastic

Front face : technoplastic

Colour
Door : smoked
Front face : white

Environment

Standards
IEC 60439-3
IEC 60695-2-11
IEC 529
IEC 60670-24
EN 50102

Quality labels
IMQ

Fire resistance
Door : 650 °C
Front face : 750 °C
Back part : 750 °C

IP degree of protection
IP40

IK degree of protection
IK07

Ambient air temperature for operation
-25...60 °C

Offer Sustainability

Sustainable offer status
Green Premium product

RoHS (date code: YYWW)
Compliant - since 0901 - Schneider Electric declaration of conformity

[Schneider Electric declaration of conformity](#)

REACH
Reference contains SVHC above the threshold - Go to CaP for more details

[Go to CaP for more details](#)

Product environmental profile
Available

[Product environmental](#)

Product end of life instructions
Need no specific recycling operations

[End of life manual](#)

Contractual warranty

Warranty period
18 months