



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	8
Number of horizontal rows	1
Type of front cover	Translucid
Width	196 mm outside
Height	198 mm outside
Depth	101.5 mm outside

### Complementary

Enclosure mounting	Surface
9 mm pitches	16
Total number of 18 mm modules	8
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 trunking flange 1 bare flange
Terminal block function	Without
Enclosure material	Back part : technoplastic Door : technoplastic Front face : technoplastic
Colour	Front face : white ( RAL 9003 ) Door : translucid
Market segment	Residential

MIP10108T

## Environment

Standards	IEC 60439-3 IEC 529 IEC 60670-24 IEC 60695-2-11 EN 50102
Quality labels	IMQ
Fire resistance	Door : 650 °C Front face : 650 °C Back part : 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations <a href="#">Product environmental</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------