



### Main

|                                 |                   |
|---------------------------------|-------------------|
| Range                           | Mini Pragma       |
| Range of product                | Mini Pragma       |
| Product or component type       | Enclosure         |
| Enclosure type                  | Modular enclosure |
| Number of 18 mm modules per row | 12                |
| Number of horizontal rows       | 2                 |
| Type of front cover             | Smoked            |
| Width                           | 268 mm outside    |
| Height                          | 353 mm outside    |
| Depth                           | 102 mm outside    |

### Complementary

|                               |   |
|-------------------------------|---|
| Enclosure mounting            | Surface   |
| 9 mm pitches                  | 24  |
| Total number of 18 mm modules | 24  |
| [In] rated current            | 63 A  |
| Type of rail                  | 35 mm asymmetrical rail   |
| Cable entry                   | 1 trunking flange<br>1 bare flange  |
| Terminal block function       | Without   |
| Enclosure material            | Back part : technoplastic<br>Door : technoplastic<br>Front face : technoplastic |
| Colour                        | Door : smoked<br>Front face : white ( RAL 9003 )                                |

### Environment

|           |                         |
|-----------|-------------------------|
| Standards | IEC 60439-3<br>EN 50102 |
|-----------|-------------------------|

MIP10212S

IEC 60670-24  
IEC 529  
IEC 60695-2-11

|                                       |  |
|---------------------------------------|--|
| Quality labels                        | IMQ  |
| Fire resistance                       | Door : 650 °C<br>Front face : 650 °C<br>Back part : 650 °C |
| IP degree of protection               | IP40   |
| IK degree of protection               | IK07   |
| Ambient air temperature for operation | -25...60 °C  |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0901 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|