



Main

| | |
|---------------------------------|-------------------|
| Range | Mini Pragma |
| Range of product | Mini Pragma |
| Product or component type | Enclosure |
| Enclosure type | Modular enclosure |
| Number of 18 mm modules per row | 4 |
| Number of horizontal rows | 1 |
| Type of front cover | Smoked |
| Width | 124 mm outside |
| Height | 198 mm outside |
| Depth | 95.5 mm outside |

Complementary

| | |
|-------------------------------|---|
| Enclosure mounting | Surface |
| 9 mm pitches | 8 |
| Total number of 18 mm modules | 4 |
| [In] rated current | 50 A |
| Type of rail | 35 mm asymmetrical rail |
| Cable entry | 1 trunking flange 1 bare flange |
| Terminal block function | Earth |
| Number of terminal blocks | 1 earth terminal block with 4 screwed outgoing |
| Distribution block outgoing | 1 x 16 mm ² for earth 1 x 6 mm ² for earth 2 x 10 mm ² for earth |
| Enclosure material | Back part : technoplastic Door : technoplastic Front face : technoplastic |
| Colour | Door : smoked Front face : white (RAL 9003) |

Environment

| | |
|-----------|----------------------------|
| Standards | IEC 60695-2-11 EN 50102 |
|-----------|----------------------------|

MIP11104S

IEC 529
IEC 60670-24
IEC 60439-3

| | |
|---------------------------------------|--|
| Quality labels | IMQ |
| Fire resistance | Door : 650 °C Front face : 750 °C Back part : 750 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -25...60 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|