



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	6
Number of horizontal rows	1
Type of front cover	Plain
Width	160 mm outside
Height	198 mm outside
Depth	95 mm outside

### Complementary

Enclosure mounting	Surface
9 mm pitches	12
Total number of 18 mm modules	6
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth
Number of terminal blocks	1 earth terminal block with 4 screwed outgoing
Distribution block outgoing	1 x 16 mm <sup>2</sup> for earth 1 x 6 mm <sup>2</sup> for earth 2 x 10 mm <sup>2</sup> for earth
Enclosure material	Back part : technoplastic Door : technoplastic Front face : technoplastic
Colour	Door : white ( RAL 9003 ) Front face : white ( RAL 9003 )

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Standards	IEC 60695-2-11 IEC 529 EN 50102 IEC 60439-3 IEC 60670-24
Quality labels	IMQ
Fire resistance	Door : 650 °C Front face : 750 °C Back part : 750 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations <a href="#">End of life manual</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------