



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	8
Number of horizontal rows	1
Type of front cover	Plain
Width	196 mm outside
Height	198 mm outside
Depth	101.5 mm outside

Complementary

Enclosure mounting	Surface
9 mm pitches	16
Total number of 18 mm modules	8
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 trunking flange 1 bare flange
Terminal block function	Earth
Number of terminal blocks	1 earth terminal block with 8 screwed outgoers
Distribution block outgoers	1 x 16 mm ² for earth 3 x 6 mm ² for earth 4 x 10 mm ² for earth
Enclosure material	Back part : technoplastic Door : technoplastic Front face : technoplastic
Colour	Door : white (RAL 9003) Front face : white (RAL 9003)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 529 EN 50102 IEC 60670-24 IEC 60439-3 IEC 60695-2-11
Quality labels	IMQ
Fire resistance	Door : 650 °C Front face : 750 °C Back part : 750 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------