



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	8
Number of horizontal rows	1
Type of front cover	Smoked
Width	196 mm outside
Height	198 mm outside
Depth	95.5 mm outside

Complementary

Enclosure mounting	Surface
9 mm pitches	16
Total number of 18 mm modules	8
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth
Number of terminal blocks	1 earth terminal block with 8 screwed outgoing
Distribution block outgoing	1 x 16 mm ² for earth 3 x 6 mm ² for earth 4 x 10 mm ² for earth
Enclosure material	Back part : technoplastic Door : technoplastic Front face : technoplastic
Colour	Door : smoked Front face : white (RAL 9003)

Environment

Standards	IEC 60695-2-11 IEC 529
-----------	---------------------------

MIP11108S

IEC 60439-3
EN 50102
IEC 60670-24

Quality labels	IMQ
Fire resistance	Door : 650 °C Front face : 750 °C Back part : 750 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------