



## Main

|                                 |                   |
|---------------------------------|-------------------|
| Range                           | Mini Pragma       |
| Range of product                | Mini Pragma       |
| Product or component type       | Enclosure         |
| Enclosure type                  | Modular enclosure |
| Number of 18 mm modules per row | 4                 |
| Number of horizontal rows       | 1                 |
| Type of front cover             | Smoked            |
| Width                           | 124 mm outside    |
| Height                          | 198 mm outside    |
| Depth                           | 95 mm outside     |

## Complementary

|                               |  |
|-------------------------------|--|
| Enclosure mounting            | Surface  |
| 9 mm pitches                  | 8  |
| Total number of 18 mm modules | 4  |
| [In] rated current            | 50 A   |
| Type of rail                  | 35 mm asymmetrical rail  |
| Cable entry                   | 1 bare flange<br>1 trunking flange   |
| Terminal block function       | Earth / neutral  |
| Number of terminal blocks     | 1 earth terminal block with 4 screwed outgoing<br>1 neutral terminal block with 4 screwed outgoing   |
| Distribution block outgoing   | 1 x 16 mm <sup>2</sup> for earth<br>1 x 16 mm <sup>2</sup> for neutral<br>1 x 6 mm <sup>2</sup> for earth<br>1 x 6 mm <sup>2</sup> for neutral<br>2 x 10 mm <sup>2</sup> for earth<br>2 x 10 mm <sup>2</sup> for neutral |
| Enclosure material            | Back part : technoplastic<br>Door : technoplastic  |

|                |   |
|----------------|---|
|                | Front face : technoplastic                                    |
| Colour         | Front face : white ( RAL 9003 )<br>Door : smoked ( RAL 9003 ) |
| Market segment | Small commercial<br>Residential                               |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | IEC 60670-24<br>EN 50102<br>IEC 60695-2-11<br>IEC 60439-3<br>IEC 529 |
| Quality labels                        | IMQ  |
| Fire resistance                       | Door : 650 °C<br>Front face : 650 °C<br>Back part : 650 °C           |
| IP degree of protection               | IP40   |
| IK degree of protection               | IK07   |
| Ambient air temperature for operation | -25...60 °C  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0901 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|