



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	8
Number of horizontal rows	1
Type of front cover	Smoked
Width	198 mm wall 222 mm outside
Height	228 mm wall 252 mm outside
Depth	98 mm total 18 mm outside 80 mm wall

Complementary

Enclosure mounting	Flush
9 mm pitches	16
Total number of 18 mm modules	8
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	Pre-cutted holes
Terminal block function	Earth
Number of terminal blocks	1 earth terminal block with 8 screwed outgoers
Distribution block outgoers	1 x 16 mm ² for earth 3 x 6 mm ² for earth 4 x 10 mm ² for earth
Enclosure material	Back part : technoplastic Door : technoplastic Front face : technoplastic
Colour	Door : smoked Front face : white (RAL 9003)

MIP 21108S

Environment

Standards	IEC 529 EN 50102 IEC 60439-3 IEC 60695-2-11 IEC 60670-24
Quality labels	IMQ
Fire resistance	Door : 650 °C Front face : 750 °C Back part : 850 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------