



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	18
Number of horizontal rows	1
Type of front cover	Smoked
Width	378 mm wall 402 mm outside
Height	228 mm wall 252 mm outside
Depth	98 mm total 18 mm outside 80 mm wall

Complementary

Enclosure mounting	Flush
9 mm pitches	36
Total number of 18 mm modules	18
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	Pre-cutted holes
Terminal block function	Earth
Number of terminal blocks	1 earth terminal block with 16 screwed outgoers
Distribution block outgoers	2 x 16 mm ² for earth 6 x 6 mm ² for earth 8 x 10 mm ² for earth
Enclosure material	Back part : technoplastic Door : technoplastic Front face : technoplastic
Colour	Door : smoked Front face : white (RAL 9003)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 60439-3 EN 50102 IEC 529 IEC 60670-24 IEC 60695-2-11
Quality labels	IMQ
Fire resistance	Door : 650 °C Front face : 750 °C Back part : 850 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------