



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	3
Type of front cover	Plain
Width	270 mm wall 294 mm outside
Height	478 mm wall 502 mm outside
Depth	98 mm total 18 mm outside 80 mm wall
Embedding depth	80 mm

### Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	36
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	Pre-cutted holes
Terminal block function	Earth
Number of terminal blocks	1 earth terminal block with 20 screwed outgoing
Distribution block outgoing	2 x 16 mm <sup>2</sup> for earth 9 x 10 mm <sup>2</sup> for earth 9 x 6 mm <sup>2</sup> for earth
Enclosure material	Back part : technoplastic

Door : technoplastic  
Front face : technoplastic

Colour Door : white ( RAL 9003 )  
Front face : white ( RAL 9003 )

## Environment

Standards IEC 60439-3  
IEC 529  
IEC 60670-24  
EN 50102  
IEC 60695-2-11

Quality labels IMQ

Fire resistance Door : 650 °C  
Front face : 750 °C  
Back part : 850 °C

IP degree of protection IP40

IK degree of protection IK07

Ambient air temperature for operation -25...60 °C

## Offer Sustainability

Sustainable offer status Green Premium product

RoHS (date code: YYWW) Compliant - since 0901 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH Reference not containing SVHC above the threshold  
[Reference not containing SVHC above the threshold](#)

Product environmental profile Available

 [Product environmental](#)

Product end of life instructions Need no specific recycling operations

 [Product environmental](#)

## Contractual warranty

Warranty period 18 months