



Main

| | |
|---------------------------------|--|
| Range | Mini Pragma |
| Range of product | Mini Pragma |
| Product or component type | Enclosure |
| Enclosure type | Modular enclosure |
| Number of 18 mm modules per row | 12 |
| Number of horizontal rows | 1 |
| Type of front cover | Plain |
| Width | 270 mm wall 294 mm outside |
| Height | 228 mm wall 252 mm outside |
| Depth | 98 mm total 18 mm outside 80 mm wall |

Complementary

| | |
|-------------------------------|--|
| Enclosure mounting | Flush |
| 9 mm pitches | 24 |
| Total number of 18 mm modules | 12 |
| [In] rated current | 63 A |
| Type of rail | 35 mm asymmetrical rail |
| Cable entry | Pre-cutted holes |
| Terminal block function | Earth / neutral |
| Number of terminal blocks | 1 earth terminal block with 8 screwed outgoing 1 neutral terminal block with 8 screwed outgoing |
| Distribution block outgoing | 1 x 16 mm ² for earth 1 x 16 mm ² for neutral 3 x 6 mm ² for earth 3 x 6 mm ² for neutral 4 x 10 mm ² for earth |

22112

| | |
|--------------------|---|
| | 4 x 10 mm ² for neutral |
| Enclosure material | Back part : technoplastic Door : technoplastic Front face : technoplastic |
| Colour | Door : white (RAL 9003) Front face : white (RAL 9003) |
| Market segment | Residential Small commercial |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 529 IEC 60439-3 IEC 60695-2-11 EN 50102 IEC 60670-24 |
| Quality labels | IMQ |
| Fire resistance | Door : 650 °C Front face : 650 °C Back part : 650 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -25...60 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations Product environmental |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|