



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Front face
Type of front plate	Plain
Accessory / separate part category	Installation accessory

### Complementary

Enclosure mounting	Flush
Type of front cover	Plain
Number of horizontal rows	1
9 mm pitches	12
Number of 18 mm modules per row	6
Total number of 18 mm modules	6
Enclosure material	Door : technoplastic Front face : technoplastic
Width	186 mm outside
Height	252 mm outside
Depth	13 mm wall 17 mm outside
Colour	Front face : white ( RAL 9003 )
Market segment	Residential

### Environment

Standards	IEC 60695-2-11 IEC 529 EN 50102
Fire resistance	Door : 650 °C Front face : 650 °C

IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations <a href="#">Product environmental</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------