



## Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Front face
Type of front plate	Transparent
Accessory / separate part category	Installation accessory

## Complementary

Enclosure mounting	Flush
Type of front cover	Translucid
Number of horizontal rows	3
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	36
Enclosure material	Door : technoplastic Front face : technoplastic
Width	294 mm outside
Height	502 mm outside
Depth	13 mm wall 18 mm outside
Colour	Front face : mist grey
Market segment	Residential Small commercial

## Environment

Standards	EN 50102 IEC 529 IEC 60695-2-11
Fire resistance	Door : 650 °C Front face : 750 °C

IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations <a href="#">Product environmental</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------