



### Main

Range of product	Mini Pragma
Product or component type	Base
Accessory / separate part category	Enclosure accessory
[In] rated current	50 A
Number of horizontal rows	1
Number of 18 mm modules per row	4
Terminal block function	Without

### Complementary

Enclosure mounting	Flush
9 mm pitches	2
Total number of 18 mm modules	4
Cable entry	Pre-cutted holes
Enclosure material	Back part : technoplastic
Width	126 mm wall
Height	228 mm wall
Depth	98 mm total 18 mm outside 80 mm wall

### Environment

Standards	IEC 60695-2-11 EN 50102
Fire resistance	Back part : 650 °C
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C
Market segment	Residential

**Offer Sustainability**

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

**Contractual warranty**

Warranty period	18 months
-----------------	-----------