



### Main

Range of product	Mini Pragma
Product or component type	Base
Accessory / separate part category	Enclosure accessory
[In] rated current	50 A
Number of horizontal rows	1
Number of 18 mm modules per row	4
Number of terminal blocks	1 earth terminal block with 8 screw outgoers
Terminal block function	Earth

### Complementary

Enclosure mounting	Flush
9 mm pitches	2
Total number of 18 mm modules	4
Cable entry	Pre-cutted holes
Distribution block outgoers	2 x (2 x 10 mm <sup>2</sup> ) for earth 2 x (2 x 16 mm <sup>2</sup> ) for earth
Enclosure material	Back part : technoplastic
Width	126 mm wall
Height	228 mm wall
Depth	98 mm total 18 mm outside 80 mm wall

### Environment

Standards	EN 50102 IEC 60695-2-11
Fire resistance	Back part : 850 °C
IK degree of protection	IK07

---

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference contains SVHC above the threshold - Go to CaP for more details <a href="#">Go to CaP for more details</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations <a href="#">Product environmental</a>

---

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---