



Main

Range of product	Mini Pragma
Product or component type	Base
Accessory / separate part category	Enclosure accessory
[In] rated current	63 A
Number of horizontal rows	1
Number of 18 mm modules per row	6
Number of terminal blocks	1 earth terminal block with 8 screw outgoers
Terminal block function	Earth

Complementary

Enclosure mounting	Flush
9 mm pitches	2
Total number of 18 mm modules	6
Cable entry	Pre-cutted holes
Distribution block outgoers	2 x (2 x 10 mm ²) for earth 2 x (2 x 16 mm ²) for earth
Enclosure material	Back part : technoplastic
Width	162 mm wall
Height	228 mm wall
Depth	98 mm total 18 mm outside 80 mm wall

Environment

Standards	IEC 60695-2-11 EN 50102
Fire resistance	Back part : 850 °C
IK degree of protection	IK07

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations Product environmental

Contractual warranty

Warranty period	18 months
-----------------	-----------
