



Main

Range of product	Mini Pragma
Product or component type	Base
Accessory / separate part category	Enclosure accessory
[In] rated current	63 A
Number of horizontal rows	2
Number of 18 mm modules per row	12
Number of terminal blocks	1 earth terminal block with 16 screw outgoing 1 neutral terminal block with 16 screw outgoing
Terminal block function	Earth / neutral

Complementary

Enclosure mounting	Flush
9 mm pitches	4
Total number of 18 mm modules	24
Cable entry	Pre-cut holes
Distribution block outgoing	2 x 16 mm ² for earth 2 x 16 mm ² for neutral 6 x 6 mm ² for earth 6 x 6 mm ² for neutral 8 x 10 mm ² for earth 8 x 10 mm ² for neutral
Enclosure material	Back part : technoplastic
Width	270 mm wall
Height	353 mm wall
Depth	98 mm total 18 mm outside 80 mm wall

MIP82212

Environment

Standards	EN 50102 IEC 60695-2-11
Fire resistance	Back part : 650 °C
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C
Market segment	Small commercial Residential

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations Product environmental

Contractual warranty

Warranty period	18 months
-----------------	-----------