



Main

| | |
|------------------------------------|--------------------|
| Range of product | Mini Pragma |
| Product or component type | Plate |
| Accessory / separate part category | Mounting accessory |
| Quantity per set | Set of 2 |

Complementary

| | |
|---------------------------------|------------------------------------|
| Enclosure mounting | Surface |
| Number of horizontal rows | 1 |
| 9 mm pitches | 16 |
| Number of 18 mm modules per row | 8 |
| Total number of 18 mm modules | 8 |
| Cable entry | 1 bare flange 1 trunking flange |
| Enclosure material | Front face : technoplastic |
| Width | 155 mm outside |
| Height | 74.5 mm outside |
| Depth | 13.5 mm outside |
| Colour | White |

Environment

| | |
|---------------------------------------|---------------------------------|
| Standards | EN 50102 IEC 60695-2-11 |
| Fire resistance | Front face : 750 °C |
| IK degree of protection | IK07 |
| Overvoltage category | II |
| Ambient air temperature for operation | -25...60 °C |
| Market segment | Residential Small commercial |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|