



Main

Range	EcoStruxure Building Expert
Product or component type	Gateway
Device application	Building automation systems
Supply	External supply : CSA
Processor name	ARM9 32-bit ,400 MHz
Battery type	Lithium

Complementary

Communication port protocol	Zigbee Pro , BACnet , Ethernet , RJ45 , 10/100 Mbit/s CANbus , 125...500 kbit/s EnOcean ,
[Us] rated supply voltage	24 V AC : 50/60 Hz : +/- 15 % 24 V DC : +/- 10 %
System requirements	Apple Safari Firefox Google Chrome Internet browser
Power consumption in W	1.6 W
Power consumption in VA	5 VA
Communication gateway	Ethernet/ZigBee
Memory capacity	64 MB flash
Mounting mode	Clip-on
Mounting support	DIN rail
Height	191 mm
Width	116 mm
Depth	45 mm
Enclosure material	ABS

Environment

Ambient air temperature for operation	60 °C
Relative humidity	90 % non-condensing

Standards	CE ICES-003 CSA C22.2
-----------	-----------------------------

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1401 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
