
Product data sheet Characteristics

MTN2313-0302

SCHUKO sock.-out. w. hng.lid, indic.lamp& label fld, shut.screwl. term. or, Sys.M



Main

Range of product	Merten System M	
Aesthetic name	M-Plan M-Elegance M-Plan glass M-Smart M-Star	
	M-Arc System M	
Product or component type	Power socket-outlet	
Device presentation	Mechanism with central plate	
Outlet standard	German	
Socket additional information	Shuttered With label surface	
Market segment	Residential Small commercial	
Complementary		
Outlet poles configuration	2P + E	
Number of gangs	1 gang	
Wiring device mounting	Flush	
Fixing mode	By screws and claws	
[ln] rated current	16 A	
[Ue] rated operational voltage	250 V	
Colour tint	Orange	
Colour code	RAL 2003	
Connections - terminals	Screwless terminals	
Material	Polycarbonate brilliant	
Environment		
IP degree of protection	IP20	
Environmental health and issues	Halogen free 3 3 3 2 2	

Complementary

Outlet poles configuration	2P + E	
Number of gangs	1 gang	
Wiring device mounting	Flush	
Fixing mode	By screws and claws	:
[In] rated current	16 A	
[Ue] rated operational voltage	250 V	
Colour tint	Orange	
Colour code	RAL 2003	
Connections - terminals	Screwless terminals	
Material	Polycarbonate brilliant	

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
Contractual warranty	