



Main

Range of product	Merten System M
Aesthetic name	System M M-Elegance M-Plan M-Star M-Arc M-Plan glass M-Smart
Product or component type	Power socket-outlet
Device presentation	Mechanism with central plate
Outlet standard	German
Socket additional information	Shuttered
Market segment	Small commercial Residential

Complementary

Outlet poles configuration	2P + E
Number of gangs	1 gang
Wiring device mounting	Flush
Fixing mode	By screws and claws
[In] rated current	16 A
[Ue] rated operational voltage	250 V
Colour tint	Polar white glossy
Colour code	RAL 9010
Connections - terminals	Screwless terminals
Material	Polycarbonate brilliant

Environment

IP degree of protection	IP20
-------------------------	------

MTN2352-0319

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
