Product data sheet Characteristics

MTN2405-0319

SCHUKO sock.-out. w. surge prot.& label fld, shut. screw term.pol.wht.glos.Sys.M





Main

Dange of product	Martan Cuatam M	
Range of product	Merten System M	
Aesthetic name	System M	
	M-Arc	
	M-Plan glass	
	M-Plan	
	M-Elegance	
	M-Star	
	M-Smart	
Product or component type	Power socket-outlet	
Device presentation	Insert with central plate	
Outlet standard	Schuko	
Socket additional information	Shuttered	

Complementary

Outlet poles configuration	2P + E	
Marking	With label surface	
Number of gangs	1 gang	
Wiring device mounting	Flush	
Fixing mode	By screws and claws	-
[In] rated current	16 A	
[Ue] rated operational voltage	250 V	· · · · · · · · · · · · · · · · · · ·
Protection type	Overvoltage protection	7
Colour tint	Polar white glossy	
Colour code	RAL 9010	<u>.</u> 9. 2
Connections - terminals	Screw terminal	
Material	Polycarbonate brilliant	9
Environment	ITN2405-0319	de:

Environment

IP degree of protection	IP20

Environmental health and issues	Halogen free	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	
Contractual warranty		
Warranty period	18 months	
Not classified OPS characteris	tics	
Market segment	Small commercial Residential	