

Product data sheet

Characteristics

MTN2405-0344

SCHUKO sock.-out. w. surge prot.& label fld, shut., screw term., wht,glos.,Sys.M



Main

| | |
|-------------------------------|--|
| Range of product | Merten System M |
| Aesthetic name | M-Arc M-Plan M-Smart M-Star M-Plan glass System M M-Elegance |
| Product or component type | Power socket-outlet |
| Device presentation | Insert with central plate |
| Outlet standard | Schuko |
| Socket additional information | Shuttered |

Complementary

| | |
|--------------------------------|-------------------------|
| Outlet poles configuration | 2P + E |
| Marking | With label surface |
| Number of gangs | 1 gang |
| Wiring device mounting | Flush |
| Fixing mode | By screws and claws |
| [In] rated current | 16 A |
| [Ue] rated operational voltage | 250 V |
| Protection type | Overvoltage protection |
| Colour tint | White glossy |
| Colour code | RAL 1013 |
| Connections - terminals | Screw terminal |
| Material | Polycarbonate brilliant |
| Surface treatment | Antibacterial |

Environment

| | |
|---------------------------------|--------------|
| IP degree of protection | IP20 |
| Environmental health and issues | Halogen free |

MTN2405-0344

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
|------------------------|---|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Not classified OPS characteristics

| | |
|----------------|---------------------------------|
| Market segment | Small commercial Residential |
|----------------|---------------------------------|
