



Main

Range of product	Merten System M
Aesthetic name	M-Arc M-Plan M-Elegance M-Star M-Smart System M M-Plan glass
Product or component type	Power socket-outlet
Device presentation	Insert with central plate
Outlet standard	German
Socket additional information	Shuttered

Complementary

Outlet poles configuration	2P + E
Function available	With switch
Local signalling	With lighting
Number of gangs	1 gang
Wiring device mounting	Flush
Fixing mode	By screw
[In] rated current	10 A 8 A
[Ue] rated operational voltage	250 V
Protection type	Miniature fuse protection
Colour tint	Aluminium
Connections - terminals	Screw terminal
Material	Polycarbonate matt
Surface treatment	Varnished

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 4Q2019 Will be compliant on 4Q2019
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Small commercial Residential
----------------	---------------------------------
