



Main

Range of product	Merten System M
Aesthetic name	M-Arc M-Elegance M-Plan M-Plan glass M-Smart M-Star System M
Product or component type	Power socket-outlet
Device presentation	Insert with central plate
Outlet standard	German
Socket additional information	Shuttered

Complementary

Outlet poles configuration	2P + E
Function available	With switch
Local signalling	With lighting
Number of gangs	1 gang
Wiring device mounting	Flush
Fixing mode	By screw
[In] rated current	10 A
[Ue] rated operational voltage	250 V
Protection type	Miniature fuse protection
Colour tint	White glossy
Colour code	RAL 1013
Connections - terminals	Screw terminal
Material	Polycarbonate brilliant

MTN501144

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1345 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------