



Main

Product or component type	Movement detector
Range of product	CONNECT
Display type	LED
Time delay	1 s...8 min
Horizontal detection angle	0...220 °
Colour tint	Polar white
Colour code	RAL 9010
Material	PC (polycarbonate) brilliant
Type of packing	Carton
IP degree of protection	IP55

Complementary

Type of setting	Area detection adjustable Light sensitivity adjustable Time adjustment
Control type	Radio frequency Remote control
Device mounting	Surface Ceiling
Mounting height	2.5 m
[Ue] rated operational voltage	230 V
Output current	16 A
Network frequency	50 Hz
Light intensity adjustment	3...1000 lux
Detection face	Frontal 16 m Lateral 14 m
Protection type	Creep zone protection
Load type	Incandescent lamp : 2000 W - 230 V AC Halogen lamp : 1200 W - 230 V AC Fluorescent tube : 1200 VA - 230 V AC Capacitive : : 10 A, 35 µF - 230 V AC

MTN5052-3119

Environment

Ambient air temperature for operation	-20...25 °C
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0834 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available