



Main

| | |
|---------------------------|----------------|
| Range of product | Merten inserts |
| Product or component type | Thermostat |
| Product destination | Room |
| Device presentation | Insert |

Complementary

| | |
|--------------------------------|----------------------------------------------|
| Function available | With thermal feedback With bimetal sensor |
| [Ue] rated operational voltage | 24 V |
| [In] rated current | 1 A |
| Measurement temperature | 5...30 °C |
| Hysteresis | 0.5 K |
| Contacts type and composition | 1 C/O |
| Height | 71 mm |
| Width | 71 mm |
| Depth | 26 mm |
| Market segment | Residential Small commercial |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Offer Sustainability

| | |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |

Reference not containing SVHC above the threshold

| | |
|-------------------------------|---------------------------------------------------|
| Product environmental profile | Available 📄 End of life manual |
|-------------------------------|---------------------------------------------------|

| | |
|----------------------------------|-----------|
| Product end of life instructions | Available |
|----------------------------------|-----------|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
