



Main

Range of product	ARGUS smoke detector
Range	ARGUS
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Colour tint	Polar white (RAL 9010)
Quantity per set	Set of 1
Type of packing	Carton
Market segment	Residential

Complementary

Power supply type	Battery
Battery type	Lithium 3.6 V
Battery life	10 yr
Detection type	Smoke
Device composition	2 screws 1 smoke detector 1 mounting base 1 dust protection foil 2 wall plugs 1 user guide
Function available	Function button Hush function Self-test of smoke detection Local alarm
Technology type	Scattered light (Tyndall effect)
Type of measurement	Optic
Noise level	85 dB at 3 m
Local signalling	Visual: LED (red) Sound: alarm Sound: signal
Material	PC (polycarbonate)

MTN5470-2119

Type of installation	Indoor
Device mounting	Ceiling Wall
Fixing mode	By screws
Diameter	112 mm
Height	49 mm
Product weight	0.149 kg

Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...60 °C
Standards	EN 14604
Directives	14/01 - vfdb directive
Quality labels	Q

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1643 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual