



### Main

Range of product	ARGUS smoke detector
Range	ARGUS
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Colour tint	Polar white (RAL 9010)
Quantity per set	Set of 1
Type of packing	Carton
Market segment	Residential

### Complementary

Power supply type	Battery
Battery type	Lithium 3.6 V
Battery life	10 yr
Detection type	Smoke
Device composition	1 mounting base 1 smoke detector 1 user guide 1 dust protection foil 2 screws 2 wall plugs
Number of devices	40
Communication network type	Wired Wireless 868 MHz
Function available	Local alarm Hush function Self-test of smoke detection Function button Alarm memory Remote alarm wired or wireless network
Number of devices	40
Operating distance	<= 100 m outdoor <= 30 m indoor
Technology type	Scattered light (Tyndall effect)
Type of measurement	Optic
Noise level	85 dB at 3 m

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	Sound: signal Visual: LED (red) Visual: LED (yellow) Sound: alarm
Type of cable	Separate twin core line
Cable distance between devices	500 m total 25 m between two devices
Cable cross section	0.5...1.5 mm <sup>2</sup> 2 wires solid
Wire stripping length	9 mm
Material	PC (polycarbonate)
Type of installation	Indoor
Device mounting	Wall Ceiling
Fixing mode	By screws
Diameter	112 mm
Height	49 mm
Product weight	0.179 kg

## Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...60 °C
Standards	EN 14604
Directives	14/01 - vfdb directive
Quality labels	Q

## Offer Sustainability

REACH	Reference contains SVHC above the threshold - Go to CaP for more details <a href="#">Go to CaP for more details</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Available <a href="#">End of life manual</a>