



Main

Range of product	ARGUS presence detector
Range	ARGUS
Product or component type	Presence detector
Load type	Halogen lamp : 2000 W - 230 V AC Motor : : 1000 VA - 230 V AC Capacitive : : 10 A, 140 µF - 230 V AC Incandescent lamp : 2200 W - 230 V AC Low voltage halogen lamp with wire-wound transformer : : 500 VA - 230 V AC Low voltage halogen lamp with electronic transformer : : 1050 VA - 230 V AC Energy saving lamp : : 100 VA
Colour tint	Polar white
Colour code	RAL 9010
Type of packing	Carton

Complementary

[Ue] rated operational voltage	220/230 V
Network frequency	50/60 Hz
[Ue] rated operational voltage	220/230 V
Input compatibility	Push-buttons and electronic insert
Input function	1 x external triggering over PL
Output current	10 A
Type of setting	Light sensitivity adjustable Time adjustment
Control type	Remote control
Function available	Master function
Time delay	10 s...30 min
Light intensity adjustment	10...1000 lux
Horizontal detection angle	0...360 °
Detection face	Radius 7 m

Material	PC (polycarbonate) with brilliant surface
Device mounting	Ceiling
Mounting height	2.5 m

Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...25 °C
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual