



Main

Range of product	ARGUS movement detector
Range	ARGUS
Product or component type	Movement detector
Load type	Capacitive : : 10 A, 140 µF - 230 V AC Incandescent lamp : 3000 W - 230 V AC Halogen lamp : 2500 W - 230 V AC
Colour tint	Polar white
Colour code	RAL 9010
Type of packing	Carton
Market segment	Residential Small commercial

Complementary

[Ue] rated operational voltage	230 V
Network frequency	50 Hz
[Ue] rated operational voltage	230 V
Output current	16 A
Protection type	Creep zone protection
Type of setting	Light sensitivity adjustable Time adjustment
Display type	LED
Time delay	1 s...8 min
Light intensity adjustment	3...1000 lux
Horizontal detection angle	0...360 °
Detection face	Frontal 16 m Lateral 10 m
Material	PC (polycarbonate) with brilliant surface
Device mounting	Ceiling
Mounting height	2.5 m

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

IP degree of protection	IP55
Ambient air temperature for operation	-20...25 °C
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0845 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------