



Main

| | |
|---------------------------|------------------|
| Range of product | KNX |
| Product or component type | Dimming actuator |
| Operating mode | KNX bus system |
| Bus type | KNX |

Complementary

| | |
|--------------------------------|---|
| Mounting support | Flush |
| [Ue] rated operational voltage | 230 V |
| Network frequency | 50/60 Hz |
| Input type | 2 x binary AC SELV |
| Number of outputs | 1 |
| Load type | LV halogen lamps : 50...210 VA (wound transformer) Incandescent lamps : 50...210 W, 230 V AC Halogen lamps : 50...210 W, 230 V AC LV halogen lamps : 50...210 W (electronic transformer) |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Offer Sustainability

| | |
|-------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |

MTN6003-0003

| | |
|----------------------------------|---|
| Product end of life instructions | Available End of life manual |
|----------------------------------|---|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Not classified OPS characteristics

| | |
|----------------|---------------------------------|
| Market segment | Residential Small commercial |
|----------------|---------------------------------|
