



Main

Range of product	KNX
Range	KNX
Aesthetic name	M-Arc M-Elegance M-Plan M-Plan glass M-Smart M-Star System M
Product or component type	Room controller
Device presentation	Insert with central cover plate
Bus type	KNX
Colour tint	Black

Complementary

Fixing mode	By 2 screws
Device mounting	Flush
Function available	Fan control Valve protection function 32 functions room controller Integrated room temperature controller Switch-on behaviour of the user interface Proximity function: for the display and the start screen Cleaning mode Background lighting Screen saver Switching, toggling, dimming Blind control Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams Pulse edges with 2-byte telegrams 8-bit linear regulator Scene retrieval Scene saving Signal function Operating modes Setpoint adjustment Controller type: 2-step controller Controller type: continuous-action PI control Controller type: switching PI control (PWM) Output: continuous in the range 0 to 100%

MTN6215-0310

Output: switching ON/OFF
All functions are displayed on a touch screen
Gesture function: the device recognises a gesture

Display type	Colour TFT display
Control type	Touch screen
Mechanical robustness	With optional anti-theft or dismantling protection
Material	Plastic
Height	71 mm
Width	71 mm
Depth	30 mm
Market segment	Residential Small commercial

Environment

IP degree of protection	IP20
-------------------------	------

Offer Sustainability

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual