

Main

Range of product	KNX
Product or component type	Switch actuator
Bus type	KNX
Number of contacts	1

Complementary



Device mounting	Flush
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
[In] rated current	16 A
Load type	Parallel compensated fluorescent lamp : <= 434 VA, 100 V AC Parallel compensated fluorescent lamp : <= 1000 VA, 230 V AC Parallel compensated fluorescent lamp : <= 1043 VA, 240 V AC Halogen lamps : <= 739 W, 100 V AC Halogen lamps : <= 1700 W, 230 V AC Halogen lamps : <= 1773 W, 240 V AC Incandescent lamps : <= 1173 W, 100 V AC Incandescent lamps : <= 2700 W, 230 V AC Incandescent lamps : <= 2817 W, 240 V AC Capacitive : 10 A - 105 µF, 100...240 V AC

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  Product environmental
Product end of life instructions	Available  End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------