



### Main

Range of product	KNX
Product or component type	Dimming actuator
Operating mode	KNX bus system
Bus type	KNX

### Complementary

18 mm pitches	6
Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50 Hz
Number of outputs	2
Load type	LV halogen lamps : 25...300 VA (wound transformer) Incandescent lamps : 25...300 W, 230 V AC Halogen lamps : 25...300 W, 230 V AC LV halogen lamps : 25...300 W (electronic transformer)

### Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0809 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>

---

Product end of life instructions	Available <a href="#">End of life manual</a>
----------------------------------	---

---

**Contractual warranty**

---

Warranty period	18 months
-----------------	-----------

---

**Not classified OPS characteristics**

---

Market segment	Residential Small commercial
----------------	---------------------------------

---