



Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	2

Complementary

Total number of 18 mm modules	2.5
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
[In] rated current	16 A
Load type	Parallel compensated fluorescent lamp : <= 1086 VA, 100 V AC Parallel compensated fluorescent lamp : <= 2500 VA, 230 V AC Parallel compensated fluorescent lamp : <= 2608 VA, 240 V AC Incandescent lamps : <= 1600 W, 100 V AC Incandescent lamps : <= 3600 W, 230 V AC Incandescent lamps : <= 3840 W, 240 V AC Halogen lamps : <= 1086 W, 100 V AC Halogen lamps : <= 2500 W, 230 V AC Halogen lamps : <= 2608 W, 240 V AC Capacitive : 16 A - 200 µF, 100...240 V AC

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

MTN647393

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------