

Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	4

Complementary

Function available	Current detection
Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50...60 Hz
[In] rated current	0.1...16 A
Load type	Parallel compensated fluorescent lamp : <= 2500 VA, 230 V AC Incandescent lamps : <= 3600 W, 230 V AC Halogen lamps : <= 2500 W, 230 V AC Capacitive : 16 A - 200 µF, 100...240 V AC Motor : <= 1000 W, 230 V AC



Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity

Schneider Electric declaration of conformity

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  Product environmental
Product end of life instructions	Available  End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------