



Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Number of contacts	2

Complementary

Total number of 18 mm modules	2.5
Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50...60 Hz
[In] rated current	10 A
Local signalling	LED
Load type	Fluorescent lamps : <= 1800 VA, 230 V AC Incandescent lamps : <= 2000 W, 230 V AC Halogen lamps : <= 1700 W, 230 V AC Capacitive : - 105 µF, 230 V AC

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0736 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Product environmental profile	Available Product environmental
-------------------------------	----------------------------------------------------

Product end of life instructions	Available End of life manual
----------------------------------	-------------------------------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Small commercial Residential
----------------	---------------------------------
