



### Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	8

### Complementary



Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50...60 Hz
[In] rated current	10 A
Local signalling	LED
Load type	Fluorescent lamps : <= 1800 VA, 230 V AC Incandescent lamps : <= 2000 W, 230 V AC Halogen lamps : <= 1700 W, 230 V AC Capacitive : - 105 µF, 230 V AC

### Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0809 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  Product environmental
Product end of life instructions	Available  End of life manual

**Contractual warranty**

Warranty period	18 months
-----------------	-----------

**Not classified OPS characteristics**

Market segment	Residential Small commercial
----------------	---------------------------------