



Main

Range of product	KNX
Product or component type	Dimming actuator
Operating mode	KNX bus system Manual
Bus type	KNX

Complementary

18 mm pitches	4
Mounting support	DIN rail
[Ue] rated operational voltage	110...230 V
Network frequency	50/60 Hz
Input type	1 x push-button : 230 V AC 1 x electronic push-button : 230 V AC
Number of outputs	1
Local signalling	LED
Load type	Incandescent lamps : 30...1000 W, 230 V AC, 50 Hz Incandescent lamps : 30...850 W, 230 V AC, 60 Hz Incandescent lamps : 14...480 W, 110 V AC, 50 Hz Incandescent lamps : 14...400 W, 110 V AC, 60 Hz Inductive : 50...1000 W, 230 V AC, 50 Hz Inductive : 50...850 W, 230 V AC, 60 Hz Inductive : 24...480 W, 110 V AC, 50 Hz Inductive : 24...400 W, 110 V AC, 60 Hz Capacitive : 50...1000 W, 230 V AC, 50 Hz Capacitive : 50...850 W, 230 V AC, 60 Hz Capacitive : 24...480 W, 110 V AC, 50 Hz Capacitive : 24...400 W, 110 V AC, 60 Hz

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

MTN649310

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0751 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------