



Main

Range of product	KNX
Product or component type	Dimming actuator
Operating mode	KNX bus system Manual
Bus type	KNX

Complementary



18 mm pitches	4
Mounting support	DIN rail
[Ue] rated operational voltage	220...230 V
Network frequency	50...60 Hz
Input type	2 x push-button : 230 V AC 2 x electronic push-button : 230 V AC
Number of outputs	2
Local signalling	LED
Load type	LV halogen lamps : 50...300 VA (wound transformer) Incandescent lamps : 30...300 W, 230 V AC Halogen lamps : 30...300 W, 230 V AC LV halogen lamps : 50...300 W (electronic transformer)

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0736 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  Product environmental
Product end of life instructions	Available  End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------